

## CAMERAS

# INDOOR IPC BULLET IPCB75G/W



### SPECIFICATIONS

Image Sensor	2 Megapixel SONY CMOS
Effective Pixels	1920(H)x1080(V)
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual 1/50~1/10000
Min. Illumination	Color: 0.1 lux /F1.4, B/W: 0.01 lux /F1.4,0 lux
S/N Ratio	>50dB
Max. IR LEDs Length	40m
Day/Night	Auto(ICR) / Color / B/W
Backlight Compensation	BLC
White Balance	Auto
Gain Control	Auto/Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas
Slow Shutter	None / Low / Middle / High
Motion Detection	22X18 areas
Focal Length	2.8-12 mm variable lens
Max Aperture	F1.4
Angle of View	H: 105°(Wide) ~ 30°(Tele)
Mount Type	Board-in Type
Lens Type	Auto Iris (DC)
Compression	H.264 High Profile / JPEG Snapshot
Resolution	50Hz Mode: 1080P(1920*1080) / 720P(1280*720) / D1(704X576) / CIF(352X288) 60Hz Mode: 1080P(1920*1080) / 720P(1280*720) / D1(704X480) / CIF(352X240)
Main Stream	1920*1080 (1 ~ 25 / 30fps)
Sub Stream	704*576 (1 ~ 25 / 30fps)
Bit Rate	H.264: 64 K ~ 8192 Kbps
Compression	G.711a / G.711u (64kbps) / PCM (128kbps)
Interface	1/1 channel In / Out
Ethernet	RJ-45 (10/100 Base-T)
Protocol	IPv4, HTTP, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP,
ONVIF	ONVIF Ver. 2.0
Max. User Access	10 users
Smart Phones	iPhone, Windows Mobile, BlackBerry, Symbian,
Browser	IE, Chrome, Firefox, Safari
Memory Slot	Micro SD, Max 32GB
Alarm	1/1 channel In/Out
Interface	1x USB / 1x RS-485
Power Supply	DC12V, PoE (802.3af)
Power Consumption	<10W
Working Environment	Temperature: -10°C~+60°C, Humidity: 10%~90%
Ingress Protection	IP 66
Dimensions	135 x 75 mm
Weight	1.4 Kg