

CAMERAS

WEATHERPROOF IPC DOME IPCD30G/W


SPECIFICATIONS

| | |
|--------------------------|--|
| Image Sensor | 2 Megapixel SONY CMOS |
| Effective Pixels | 1920(H)x1080(V) |
| Scanning System | Progressive |
| Electronic Shutter Speed | Auto/Manual 1/50~1/10000 |
| Min. Illumination | Color: 0.1 lux /F1.4, B/W: 0.01 lux /F1.4, 0 lux (IR) |
| S/N Ratio | >50dB |
| Max. IR LEDs Length | 30m |
| Day/Night | Auto(ICR) / Color / B/W |
| Backlight Compensation | BLC |
| White Balance | Auto |
| Gain Control | Auto/Manual |
| Noise Reduction | 3D |
| Privacy Masking | Up to 4 areas |
| Slow Shutter | None / Low / Middle / High |
| Motion Detection | 22X18 areas |
| Focal Length | 3.6mm fixed lens |
| Max Aperture | F1.4 |
| Angle of View | H: 105°(Wide) ~ 30°(Tele) |
| Mount Type | Board-in Type |
| Lens Type | Auto Iris (DC) |
| Compression | H.264 High Profile / JPEG Snapshot |
| Resolution | 50Hz Mode: 1080P(1920*1080) / 720P(1280*720) / 60Hz Mode: 1080P(1920*1080) / 720P(1280*720) / |
| Main Stream | 1920*1080 (1 ~ 25 / 30fps) |
| Sub Stream | 704*576 (1 ~ 25 / 30fps) |
| Bit Rate | H.264: 64 K ~ 8192 Kbps |
| Compression | G.711a / G.711u (64kbps) / PCM (128kbps) |
| Interface | 1/1 channel In / Out |
| Ethernet | RJ-45 (10/100 Base-T) |
| Protocol | IPv4, HTTP, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, |
| ONVIF | ONVIF Ver. 2.0 |
| Max. User Access | 10 users |
| Smart Phones | iPhone, Windows Mobile, BlackBerry, Symbian, |
| Browser | IE、 Chrome、 Firefox、 Safari |
| Memory Slot | Micro SD, Max 32GB |
| Alarm | 1/1 channel In/Out |
| Interface | 1x USB / 1x RS-485 |
| Power Supply | DC12V, PoE (802.3af) |
| Power Consumption | <10W |
| Working Environment | Temperature: -10°C~+60°C, Humidity: 10%~90% |
| Ingress Protection | IP 66 |