

24CH NVR

NVR24CHS



SPECIFICATIONS

SPECIFICATIONS		
System	main processor	Hi3535
	operating system	embedded linux
	system resources	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
Interface	user interface	support 16-bit true color graphical menu interface and mouse operation
	preview screen	1/4/8/16/24/32
Video	video standards	PAL (625line, 50f/s) ; NTSC (525line, 60f/s)
	Videocompression	H.264(Main Profile)
	display quality	monitor : D1 ; VGA, HDMI : HD
	play quality	3.0mega pixel/1080P/720P
	Video access	8*5M/16*3M/24*1080P/32*960P
	motion detect	support
Audio	audio compression	G.711A
	bidirectional talk	support
Record&playback	record mode	manual>alarm>motion detection>timing
	local playback	2ch(5M)/4ch(3M)/4ch (1080P) /8ch(960P)real-time
	search mode	Time/calendar/event/channel search
Storage&backup	space occupation	Video: 1080p 80G/day/ch, 720p 26G/day/ch, 960H 24G/day/ch, D1 16~20G/day/ch ; Audio: 691.2M/day/channel
	record storage	HDD,network
	backup mode	Network backup,USB HDD,USB writer,SATA writer
Interface	video input	RJ45
	video output	1ch VGA、 1ch HDMI HD output
	audio input	1ch RCA
	audio output	1ch RCA
	alarm input	no
	alarm output	no
	net interface	1*RJ45 10M/100M /1000M(optional poe)
	PTZ control	1*RS485, support 18 kinds of PTZ protocols
	USB	2*USB2.0 (reserve 2 front-end interface)
	HDD	2* SATA (max.4T per one) , 1*ESATA
	Power supply	12V/4A
	dimension	350mm(length)* 295mm(width)* 45mm(high)
Other	ONVIF	support