

## WEATHERPROOF IPC PTZ PTZIP8603



Specifications	
Image Processor	CMOS
Image Sensor	2 megapixel
IR Range	100m
Zoom	18X optical and digital zoom
Low Illumination	Colour mode: 0.05-1 Lux @ F1.2(30IRE, AGC ON) B/W Mode: 0.005-0.1 Lux @ F1.2 (30IRE, AGC ON)
S/N Ratio	70.1dB/83.5dB/90dB/110dB
Electronic Shutter	NTSC: 1/30-1/8,000 s; PAL 1/25-1/8,000s
AGC	ON/OFF
BLC	ON/OFF
White Balance	Auto/Manual
Auto Iris Control	DC drive
Video System	NTSC/PAL optional
Lens Mount	C/CS
Video Compression	H.264 dual streaming/MJPEG
Maximum Frame	NTSC: 30fps; PAL: 25fps
Output bit rate	128Kbps-6Mbps
Maximum Resolution	1920 x 1080, 1280 x 720 @ 30fps
Deputy Stream	PAL: 1280 x 720, 640 x 480, 352 x 288
Audio Compression	G.711
Audio Input	1-Ch, line level, impedance: 1k?
Audio Output	1-Ch, line level, impedance: 600k?
Motion Detection	Support
Password protection	Support
Network	1 of RJ45 10/100M adaptive to POE
Network Protocol	TCP/IP, HTTP, ICMP, PPPoE, DHCP, UDP, SMTP, RTP, RTSP, SNMP, ARP
Alarm input	2-way semaphore
Alarm output	1-way, switch
Network remote upgrade	Support
Power supply	PoE/12VDC/24VAC
Working Temperature	10°C-50°C
Working Humidity	0-90% (non-condensing)